



65 SERIES AG RADIAL

WITH THE POWER OF CTR*

FEATURE

- Tilted lug tip

BENEFIT

- Lesser vibration and noise

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Mud breaker

BENEFIT

- Better self cleaning

FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- Rounded shoulder

BENEFIT

- Lesser damage to soil and crop

FEATURES

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



*Lower Compaction, Higher Traction and Better Roadability

LIST OF SIZES

SIZE	LI/SI
440/65 R 24	128 D
440/65 R 24	135 D
480/65 R 24	133 D
480/65 R 24	140 D
540/65 R 24	140 D
540/65 R 24	146 D
440/65 R 28	138 D
480/65 R 28	136 D
480/65 R 28	142 D
540/65 R 28	142 D
540/65 R 28	149 D
600/65 R 28	147 D
600/65 R 28	154 D
540/65 R 30	143 D
540/65 R 30	150 D
540/65 R 34	145 D
540/65 R 34	152 D
600/65 R 34	151 D
600/65 R 34	157 D
540/65 R 38	147 D
540/65 R 38	153 D
600/65 R 38	153 D
650/65 R 38	157 D
650/65 R 38	163 D
650/65 R 42	158 D
650/65 R 42	165 D

All tyres conform to ETRTO & TRA standards. Sizes available as of 01/2019.

CEAT
SPECIALTY

HARD WORKING TYRES

CEAT Specialty Tyres B.V
Joop Geesinkweg 901, 1114 AB Amsterdam – Duivendrecht
Website: www.ceatspecialty.com
Email: cstbv@ceat.com