

FARMAX R70 AG RADIAL

CEAT
SPECIALTY

WITH THE POWER OF CTR*

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction

FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop

FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction



*Lower Compaction, Higher Traction and Better Roadability

LIST OF SIZES

SIZE	LI/SS	SIZE	LI/SS
200/70 R 16	94 A8/B	600/70 R 28	161 A8/B
240/70 R 16	104 A8/B	420/70 R 30	134 A8/B
260/70 R 20	113 A8/B	480/70 R 30	141 A8/B
280/70 R 16	112 A8/B	480/70 R 30	147 D
280/70 R 18	114 A8/B	480/70 R 30	150 A8
280/70 R 20	116 A8/B	520/70 R 30	145 A8/B
300/70 R 20	110 A8/B	600/70 R 30	152 A8/B
300/70 R 20	120 A8/B	600/70 R 30	158 A8/B
320/70 R 20	113 A8/B	480/70 R 34	143 A8/B
320/70 R 20	123 A8/B	480/70 R 34	149 A8/B
360/70 R 20	120 A8/B	480/70 R 34	155 A8/B
360/70 R 20	129 A8/B	520/70 R 34	148 A8/B
380/70 R 20	122 A8/B	520/70 R 34	168 A8/B
380/70 R 20	132 A8/B	480/70 R 38	145 A8/B
320/70 R 24	116 A8/B	520/70 R 38	150 A8/B
360/70 R 24	122 A8/B	520/70 R 38	150 D
380/70 R 24	125 A8/B	520/70 R 38	153 A8
380/70 R 24	125 D	580/70 R 38	155 A8/B
380/70 R 24	128 A8	580/70 R 38	170 A8/B
420/70 R 24	130 A8/B	580/70 R 38	180 A8/B
420/70 R 24	130 D	710/70 R 38	172 A8/B
420/70 R 24	133 A8	710/70 R 38	178 A8/B
480/70 R 24	138 A8/B	710/70 R 38	178 D
320/70 R 28	119 A8/B	710/70 R 38	181 A8
360/70 R 28	125 A8/B	580/70 R 42	158 A8/B
380/70 R 28	127 A8/B	580/70 R 42	158 D
420/70 R 28	133 A8/B	580/70 R 42	161 A8
420/70 R 28	133 D	620/70 R 42	166 A8/B
420/70 R 28	136 A8	620/70 R 42	173 A8/B
480/70 R 28	140 A8/B	710/70 R 42	173 A8/B
480/70 R 28	151 A8/B		

All tyres conform to ETRTO & TRA standards. Sizes available as of 12/2020.