

85/80/70 SERIES AG RADIAL

WITH THE POWER OF CTR* 480/80R46 FARMAX R80

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- Rounded shoulder

BENEFIT

- Lesser damage to soil and crop

FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

FEATURE


- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction

MACHINERY

- 2WD Tractor
- 4WD Tractor
- MFVA (Mechanical front wheel assist)



TECHNICAL SPECIFICATION

SIZE	480/80R46
PATTERN	FARMAX R85
TREAD DESIGN	TRACTOR R1W
TT/TL	TL

Size	Rim	Infl tire dimension		Static Loaded	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD	radius				Speed, km/h (mph)						
		mm <i>in</i>	mm <i>in</i>	mm <i>in</i>	mm <i>in</i>	Speed Symbol	bar <i>psi</i>	Static	10 6	20 12	30 19	40 25	50 31	
480/80R46	DW16L	485 19.1	1940 76.4	900 35.4	5800 228.3		1.3	6830	4460	3650	3180	2970	2970	
							19	15040	9820	8040	7000	6540	6540	
							1.6	7710	5030	4120	3580	3350	3350	
							23	16980	11080	9070	7890	7380	7380	
							2.0	8790	5730	4700	4090	3820	3820	
							29	19360	12620	10350	9010	8410	8410	
							158 A8	2.4	9780	6380	5230	4550	4250	4250
							158 B	35	21540	14050	11520	10020	9360	9360

All tires confirms ETRTO T&RA & STRO standards



CEAT Limited Is One Of The Leading Manufacturers Established In 1958 CEAT Is A Part Of RPG Enterprises, Among The Top 5 Business Houses In India With A Group Turn Over Of USD 2.5billion. CEAT 57 Years Of Experience, CEAT serves customers in 102 countries across 5 plants and wide range of tires in all segments like Truck Bus Bias and Radial, SUV, Passengers, 2&3 Wheelers, Floatation, Mining, Earthmover, Farm and Other Special Application off the Road Tires.