

85/80/70 SERIES AG RADIAL

WITH THE POWER OF CTR* 460/85R38 FARMAX R85

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- Rounded shoulder

BENEFIT

- Lesser damage to soil and crop

FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

FEATURE


- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction

MACHINERY

- 2WD Tractor
- 4WD Tractor
- MFVA (Mechanical front wheel assist)



TECHNICAL SPECIFICATION

SIZE	460/85R38
PATTERN	FARMAX R85
TREAD DESIGN	TRACTOR R1W
TT/TL	TL

Size	Rim	Infl tire dimension		Static Loaded	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD	radius				Speed, km/h (mph)						
		mm <i>in</i>	mm <i>in</i>	mm <i>in</i>	mm <i>in</i>	Speed Symbol	bar <i>psi</i>	Static	10 6	20 12	30 19	40 25	50 31	
460/85R38	W16L	480 18.9	1747 68.8	803 31.6	5213 205.2			0.8	4990	3260	2670	2320	2170	2170
								12	10990	7180	5880	5110	4780	4780
	1.0							5680	3710	3040	2640	2470	2470	
	15							12510	8170	6700	5810	5440	5440	
	1.3							6620	4320	3540	3080	2880	2880	
	19							14580	9520	7800	6780	6340	6340	
	149 A8	1.6	7480	4880	4000	3480	3480	3250	3250					
	149 B	23	16480	10750	8810	7670	7160	7160						

All tires confirms ETRTO T&RA & STRO standards



CEAT Limited Is One Of The Leading Manufacturers Established In 1958 CEAT Is A Part Of RPG Enterprises, Among The Top 5 Business Houses In India With A Group Turn Over Of USD 2.5billion. CEAT 57 Years Of Experience, CEAT serves customers in 102 countries across 5 plants and wide range of tires in all segments like Truck Bus Bias and Radial, SUV, Passengers, 2&3 Wheelers, Floatation, Mining, Earthmover, Farm and Other Special Application off the Road Tires.