

65 SERIES AG RADIAL

WITH THE POWER OF CTR*

540/65R24 FARMAX R65

FEATURE

- Tilted lug tip

BENEFIT

- Lesser vibration and noise

FEATURE

- Mud breaker

BENEFIT

- Better self cleaning

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

FEATURE

- Rounded shoulder

BENEFIT

- Lesser damage to soil and crop

FEATURES


- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction

MACHINERY

- 2WD Tractor
- 4WD Tractor
- Combine Harvester
- MFWA (Mechanical front wheel assist)



TECHNICAL SPECIFICATION

SIZE	540/65R24
PATTERN	FARMAX R65
TREAD DESIGN	TRACTOR R1W
TT/TL	TL

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	PR, Stars Load Index	Infl. Press	Recommend load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
								Non cyclic operation				Cyclic operation			
		mm / in	mm / in					mm / in	mm / in	Speed	bar	Field operation	25	40	50
					Symbol	psi						psi			
540/65R24	W16L, W18L	550	1312	590	3860	146D	0.8	1820	1870	1730	1660	1580	1	2690	2450
							12	4010	4120	3810	3660	3480	15	5930	5400
		21.7	51.7	23	152		1.0	2070	2130	1970	1890	1800	1.25	3060	2790
							15	4560	4690	4340	4160	3960	18	6740	6150
							1.3	2420	2490	2300	2210	2100	1.625	3570	3260
							19	5330	5480	5070	4870	4630	24	7860	7180
							2.4	3450	3560	3290	3150	3000	3	5100	4650
							35	7600	7840	7250	6940	6610	44	11230	10240

All tires confirms ETRTO T&RA & STRO standards



CEAT Limited Is One Of The Leading Manufacturers Established In 1958 CEAT Is A Part Of RPG Enterprises, Among The Top 5 Business Houses In India With A Group Turn Over Of USD 2.5billion. CEAT 57 Years Of Experience, CEAT serves customers in 102 countries across 5 plants and wide range of tires in all segments like Truck Bus Bias and Radial, SUV, Passengers, 2&3 Wheelers, Floatation, Mining, Earthmover, Farm and Other Special Application off the Road Tires.