

65 SERIES AG RADIAL

CEAT
SPECIALTY

WITH THE POWER OF CTR*

600/65R28 FARMAX R65 147D

FEATURE

- Tilted lug tip

BENEFIT

- Lesser vibration and noise

FEATURE

- Mud breaker

BENEFIT

- Better self cleaning

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

FEATURE

- Rounded shoulder

BENEFIT

- Lesser damage to soil and crop

FEATURES


- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction

MACHINERY

2WD Tractor
4WD Tractor
Combine Harvester
MFWA (Mechanical front wheel assist)



TECHNICAL SPECIFICATION

SIZE	600/65R28
PATTERN	FARMAX R65
TREAD DESIGN	TRACTOR R1W
TT/TL	TL

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	PR,Stars Load Index	Infl. Press	Recommend load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
								Non cyclic operation				Cyclic operation			
								mm / in	mm / in	mm / in	mm / in	Speed	bar	Field operation	25
						Symbol	psi						psi		
600/65R28	DW20B ,W18L	591 23.3	1491 58.7	668 26	4473 176	147D	0.8	2350	2420	2230	2140	2040	1	3470	3160
							12	5180	5330	4910	4710	4490	15	7640	6960
							1	2680	2760	2550	2450	2330	1.25	3960	3610
							15	5900	6080	5620	5400	5130	18	8720	7950
							1.3	3130	3220	2980	2860	2720	1.63	4620	4220
							19	6890	7090	6560	6300	5990	24	10180	9300
							1.6	3540	3640	3370	3230	3075	2	5230	4770
							23	7800	8020	7420	7110	6770	29	11520	10510

All tires confirms ETRTO T&RA & STRO standards



CEAT Limited Is One Of The Leading Manufacturers Established In 1958 CEAT Is A Part Of RPG Enterprises, Among The Top 5 Business Houses In India With A Group Turn Over Of USD 2.5billion. CEAT 57 Years Of Experience, CEAT serves customers in 102 countries across 5 plants and wide range of tires in all segments like Truck Bus Bias and Radial, SUV, Passengers, 2&3 Wheelers, Floatation, Mining, Earthmover, Farm and Other Special Application off the Road Tires.