

85/80/70 SERIES AG RADIAL

WITH THE POWER OF CTR* **580/70R38 FARMAX R70**

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- Rounded shoulder

BENEFIT

- Lesser damage to soil and crop

FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

FEATURE


- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction

MACHINERY

- 2WD Tractor
- 4WD Tractor
- MFVA (Mechanical front wheel assist)



TECHNICAL SPECIFICATION

SIZE	580/70R38
PATTERN	FARMAX R70
TREAD DESIGN	TRACTOR R1W
TT/TL	TL

Size	Rim	Inflated tire		Loaded	Rolling	PR,Stars	Inf.	Recommend load, kg (lbs)					
		dimension		Static	Circum	Load	Press.	Speed, km/h (mph)					
		SW	OD	Radius		Index		Satatic	10	20	30	40	50
		mm	mm	mm	mm	Speed	bar						
		in	in	in	in	Symbol	psi						
580/70 R38	W18L	577 22.72	1827 71.93	832 32.7	5420 213.4	155A8/B	0.8	5930	3870	3170	2760	2580	2580
							12	13060	8520	6980	6080	5680	5680
							1	6760	4410	3620	3150	2940	2940
							15	14890	9710	7970	6940	6480	6480
							1.3	7890	5150	4220	3670	3430	3430
							19	17380	11340	9300	8080	7560	7560
							1.6	8910	5810	4770	4150	3875	3875
							23	19630	12800	10510	9140	8540	8540

All tires confirms ETRTO T&RA & STRO standards



CEAT Limited Is One Of The Leading Manufacturers Established In 1958 CEAT Is A Part Of RPG Enterprises. Among The Top 5 Business Houses In India With A Group Turn Over Of USD 2.5billion. CEAT 57 Years Of Experience, CEAT serves customers in 102 countries across 5 plants and wide range of tires in all segments like Truck Bus Bias and Radial, SUV, Passengers, 2&3 Wheelers, Floatation, Mining, Earthmover, Farm and Other Special Application off the Road Tires.