

# FARMAX R70

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
520/70R38	150A8/B	TL	W15L W16L W18L	530 20.9	1749 68.9	800 31.5	5204 204.9	0.8	5150	3360	2760	2400	2240	2240
								12	11340	7400	6080	5290	4930	4930
								1	5870	3830	3140	2730	2550	2550
								15	12930	8440	6920	6010	5620	5620
								1.3	6830	4460	3650	3180	2970	2970
								19	15040	9820	8040	7000	6540	6540
								1.6	7710	5030	4120	3580	3350	3350
								23	16980	11080	9070	7890	7380	7380