

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph								
				SW	OD				Static	10	20	30	40	50			
				mm	mm					6	12	19	25	31			
480/70R38	145 A8/B	TL	W14L W15L W16L	500	1680	773	5013	bar	Recommend load kg /lbs								
									mm	in	psi	4440	2900	2370	2070	1930	1930
									in	in	psi	9780	6390	5220	4560	4250	4250
									in	in	psi	5060	3300	2710	2350	2200	2200
									in	in	psi	11150	7270	5970	5180	4850	4850
									in	in	psi	5910	3860	3160	2750	2570	2570
									in	in	psi	13020	8500	6960	6060	5660	5660
									in	in	psi	6670	4350	3220	3100	2900	2900
in	in	psi	14690	9580	7090	6830	6390	6390									

All tires confirms ETRTO T&RA & STRO standards