

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
									Recommend load kg /lbs					
520/70R30	145 A8/B	TL	W15L W16L W18L	530 20.9	1536 60.5	694 27.3	4537 178.6	0.8	4440	2900	2370	2070	1930	1930
								12	9780	6390	5220	4560	4250	4250
								1	5060	3300	2710	2350	2200	2200
								15	11150	7270	5970	5180	4850	4850
								1.3	5910	3860	3160	2750	2570	2570
								19	13020	8500	6960	6060	5660	5660
								1.6	6670	4350	3570	3100	2900	2900
								23	14690	9580	7860	6830	6390	6390