

# FARMAX R70

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
									Recommend load kg /lbs					
420/70R28	133 A8/B	TL	W12 W13 W14L	430 16.9	1349 53.1	614 24.2	3985 156.9	0.8	3150	2060	1690	1470	1370	1370
								12	6940	4540	3720	3240	3020	3020
								1	3590	2340	1920	1670	1560	1560
								15	7910	5150	4230	3680	3440	3440
								1.3	4190	2730	2240	1950	1820	1820
								19	9230	6010	4930	4300	4010	4010
								1.6	4740	3090	2530	2200	2060	2060
								23	10440	6810	5570	4850	4540	4540