

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

| Size | LI/SS | Type | Rim | Unloaded Dimension | | SLR | RC | Infl.Press | Speed kmph /mph | | | | | |
|-----------|----------|------|------------------|--------------------|------|-----|------|------------|------------------------|------|------|------|------|------|
| | | | | SW | OD | | | | Static | 10 | 20 | 30 | 40 | 50 |
| | | | | mm | mm | | | | | 6 | 12 | 19 | 25 | 31 |
| | | | | mm | mm | mm | mm | bar | Recommend load kg /lbs | | | | | |
| | | | | in | in | in | in | psi | | | | | | |
| 320/70R28 | 119 A8/B | TL | W9 W10 W11 | 320 | 1190 | 550 | 3562 | 0.8 | 2090 | 1370 | 1120 | 970 | 910 | 910 |
| | | | | | | | | 12 | 4600 | 3020 | 2470 | 2140 | 2000 | 2000 |
| | | | | | | | | 1 | 2370 | 1550 | 1270 | 1100 | 1030 | 1030 |
| | | | | | | | | 15 | 5220 | 3410 | 2800 | 2420 | 2270 | 2270 |
| | | | | | | | | 1.3 | 2760 | 1800 | 1480 | 1280 | 1200 | 1200 |
| | | | | | | | | 19 | 6080 | 3960 | 3260 | 2820 | 2640 | 2640 |
| | | | | | | | | 1.6 | 3130 | 2040 | 1670 | 1460 | 1360 | 1360 |
| | | | | | | | | 23 | 6890 | 4490 | 3680 | 3220 | 3000 | 3000 |