

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed, km/h (mph)									
				SW	OD				Static	10	20	30	40	50				
				mm/in	mm/in					6	12	19	25	31				
												Recommend load kg /lbs						
480/70R24	138 A8/B	TL	W14L	490	1316	591	3871	0.8	3610	2360	1930	1680	1570	1570				
								12	7950	5200	4250	3700	3460	3460				
			W15L					19.3	51.8	23.3	152.4	1	4120	2690	2200	1920	1790	1790
												15	9070	5930	4850	4230	3940	3940
			W16L									1.3	4810	3140	2570	2240	2090	2090
												19	10590	6920	5660	4930	4600	4600
1.6	5430	3540	2900	2530	2360	2360												
23	11960	7800	6390	5570	5200	5200												