

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph						
				SW	OD				Static	10	20	30	40	50	
				mm	mm					6	12	19	25	31	
360/70R24	122 A8/B	TL	W12 W11 W10	360	1152	524	3418	134.6	Recommend load kg /lbs						
									0.8	2300	1500	1230	1070	1000	1000
									12	5070	3300	2710	2360	2200	2200
									1	2620	1710	1400	1220	1140	1140
									15	5770	3770	3080	2690	2510	2510
									1.3	3060	2000	1640	1420	1330	1330
									19	6740	4410	3610	3130	2930	2930
									1.6	3450	2250	1850	1610	1500	1500
23	7600	4960	4070	3550	3300	3300									

All tires confirms ETRTO T&RA & STRO standards