

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
300/70R20	120 A8/B	TL	W9 W10	295 11.6	952 37.5	434 17.1	2826 111.3	1.3	2250	1470	1210	1050	980	980
								19	4960	3240	2670	2310	2160	2160
								1.6	2530	1650	1350	1180	1100	1100
								23	5570	3630	2970	2600	2420	2420
								2	2900	1890	1550	1350	1260	1260
								29	6390	4160	3410	2970	2780	2780
								2.4	3220	2100	1720	1500	1400	1400
								35	7090	4630	3790	3300	3080	3080

All tires confirms ETRTO T&RA & STRO standards