

# FARMAX R70

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
280/70R20	116 A8/B	TL	W10 W9	290 11.4	900 35.4	413 16.3	2682 105.6	1.2	1910	1250	1020	890	830	830
								17	4210	2750	2250	1960	1830	1830
								1.6	2280	1490	1220	1060	990	990
								23	5020	3280	2690	2330	2180	2180
								2	2580	1680	1380	1200	1120	1120
								29	5680	3700	3040	2640	2470	2470
								2.4	2880	1880	1540	1340	1250	1250
								35	6340	4140	3390	2950	2750	2750