

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
260/70R20	113 A8/B	TL	W9 W8	260	872	401	2605	1.2	1770	1160	950	820	770	770
								17	3900	2560	2090	1810	1700	1700
								1.6	2090	1370	1120	970	910	910
								23	4600	3020	2470	2140	2000	2000
								2	2370	1550	1270	1100	1030	1030
								29	5220	3410	2800	2420	2270	2270
								2.4	2650	1730	1410	1230	1150	1150
								35	5840	3810	3110	2710	2530	2530

All tires confirms ETRTO T&RA & STRO standards