FARMAX R85



FEATURE • Greater lug overlap **FEATURES** BENEFITS • Reduced space between lugs • Mud breaker at the centre • More lugs in footprint Better stability **BENEFITS** Better roadability · Increased service life • Self cleaning FEATURE • Larger inner volume FEATURE BENEFITS · Rounded shoulder • Reduced soil compaction BENEFIT Increased load · Less soil disturbance carrying capacity FEATURE • Dual lug angle **BENEFITS** MACHINERY Superior traction Better Roadability FEATURE \bigcirc \bigcirc • Wider tread BENEFITS

Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				SW	OD	δĽN	nu	IIII. Fress	Static	10	20	30	40	50
									otatic	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	Teconiniena toda ky / ibs					
520/85R38	169A8/B	TL						2.4	10510	6860	5620	4890	4570	4570
								35	23150	15110	12380	10770	10070	10070
							2.8	11500	7500	6150	5350	5000	5000	
			DW16L	530	1855	847	5513	41	25330	16520	13550	11780	11010	11010
			DW18L	20.9	<u>).9</u> 73	33.3	217.1	3.2	12440	8120	6650	5790	5410	5410
								46	27400	17890	14650	12750	11920	11920
								3.6	13340	8700	7130	6210	5800	5800
								52	29380	19160	15700	13680	12780	12780

Reduced soil compactionIncreased footprint

All tires confirms ETRTO T&RA & STRO standards