

FARMAX R85

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- · Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance


FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	JLN	ΝŪ	IIII. FIESS	Static	10	20	30	40	50
									Otatio	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	necomment toda kg/ibs					
320/85R38	143A8/B	F	W11 W10 W9	325 12.8	1510 59.4	703 27.7	4543 178.9	2.4	4950	3230	2640	2300	2150	2150
								35	10900	7110	5810	5070	4740	4740
								2.8	5410	3530	2890	2510	2350	2350
								41	11920	7780	6370	5530	5180	5180
								3.2	5840	3810	3120	2720	2540	2540
								46	12860	8390	6870	5990	5590	5590
								3.6	6270	4090	3350	2920	2725	2725
								52	13810	9010	7380	6430	6000	6000

All tires confirms ETRTO T&RA & STRO standards