

FARMAX R85

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- · Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance

FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	JLN	nu	IIII. FI633	Static	10	20	30	40	50
									Otatio	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	necomment toda ky / ibs					
460/85R34	147 A8/B	TL	W16L W15L W14L	480 18.9	1646 64.8	752 29.6	4895 192.7	0.8	4720	3080	2520	2190	2050	2050
								12	10400	6780	5550	4820	4520	4520
								1	5380	3510	2880	2500	2340	2340
								15	11850	7730	6340	5510	5150	5150
								1.3	6260	4080	3350	2910	2720	2720
								19	13790	8990	7380	6410	5990	5990
								1.6	7070	4610	3780	3290	3075	3075
								23	15570	10150	8330	7250	6770	6770

All tires confirms ETRTO T&RA & STRO standards