

FARMAX R85

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

| Size | LI/SS | Type | Rim | Unloaded Dimension | | SLR | RC | Infl. Press | Speed, kmph (mph) | | | | | |
|-----------|----------|------|------|--------------------|-------|------|-------|-------------|-------------------|------|------|------------------------|------|------|
| | | | | SW | OD | | | | Static | 10 | 20 | 30 | 40 | 50 |
| | | | | mm/in | mm/in | | | | | 6 | 12 | 19 | 25 | 31 |
| | | | | | | | | | | | | Recommend load kg /lbs | | |
| 420/85R28 | 139 A8/B | TL | W15L | 450 | 1425 | 648 | 4224 | 0.8 | 3730 | 2430 | 1990 | 1730 | 1620 | 1620 |
| | | | | | | | | 12 | 8220 | 5350 | 4380 | 3810 | 3570 | 3570 |
| | | | W14L | 17.7 | 56.1 | 25.5 | 166.3 | 1 | 4260 | 2780 | 2280 | 1980 | 1850 | 1850 |
| | | | | | | | | 15 | 9380 | 6120 | 5020 | 4360 | 4070 | 4070 |
| | | | W13 | | | | | 1.3 | 4950 | 3230 | 2640 | 2300 | 2150 | 2150 |
| | | | | | | | | 19 | 10900 | 7110 | 5810 | 5070 | 4740 | 4740 |
| | | | | | | | | 1.6 | 5590 | 3650 | 2990 | 2600 | 2430 | 2430 |
| | | | | | | | | 23 | 12310 | 8040 | 6590 | 5730 | 5350 | 5350 |