

# FARMAX R85

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed, kmph (mph)					
				SW	OD				Static	10	20	30	40	50
				mm/in	mm/in					6	12	19	25	31
									Recommend load kg /lbs					
340/85R28	127 A8/B	TL	W12	355	1289	592	3846	0.8	2690	1760	1440	1250	1170	1170
								12	5930	3880	3170	2750	2580	2580
								1	3060	2000	1640	1420	1330	1330
								15	6740	4410	3610	3130	2930	2930
			W11	14	50.7	23.3	151.4	1.3	3570	2330	1910	1660	1550	1550
								19	7860	5130	4210	3660	3410	3410
								1.6	4030	2630	2150	1870	1750	1750
								23	8880	5790	4740	4120	3850	3850