FARMAX R85



FEATURE • Greater lug overlap **FEATURES** BENEFITS • Reduced space between lugs • Mud breaker at the centre • More lugs in footprint Better stability **BENEFITS** Better roadability · Increased service life • Self cleaning FEATURE • Larger inner volume FEATURE BENEFITS · Rounded shoulder • Reduced soil compaction BENEFIT Increased load · Less soil disturbance carrying capacity FEATURE • Dual lug angle **BENEFITS** MACHINERY Superior traction Better Roadability FEATURE \bigcirc \bigcirc • Wider tread BENEFITS

Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				SW	OD	δLN	nu	IIII. Fress	Static	10	20	30	40	50
									olulio	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	noooniniona lodu ky / hos					
250/85R28	112A8/B	TL	W8 W7 W9	250 9.84	1137 44.76	526 20.72	3340 131.5	0.8	1730	1130	920	800	750	750
								12	3810	2490	2030	1760	1650	1650
								1	1960	1280	1050	910	850	850
								15	4320	2820	2310	2000	1870	1870
								1.3	2280	1490	1220	1060	990	990
								19	5020	3280	2690	2330	2180	2180
								1.6	2580	1680	1380	1200	1120	1120
								23	5680	3700	3040	2640	2470	2470

Reduced soil compactionIncreased footprint

All tires confirms ETRTO T&RA & STRO standards