

# FARMAX R85

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
320/85R24	142A8/B	TL	W11 W10 W9	325 12.8	1154 45.4	525 20.7	3423 134.8	3	4990	3260	2670	2320	2170	2170
								44	10990	7180	5880	5110	4780	4780
								3.4	5380	3510	2880	2500	2340	2340
								49	11850	7730	6340	5510	5150	5150
								3.8	5750	3750	3080	2680	2500	2500
								55	12670	8260	6780	5900	5510	5510
								4.2	6100	3980	3260	2840	2650	2650
								61	13440	8770	7180	6260	5840	5840

All tires confirms ETRTO T&RA & STRO standards