

FARMAX R85

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance

FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	JLII	no	IIII. FICSS	Static	10	20	30	40	50
									Otatio	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	necomment toda kg/ibs					
320/85R24	122 A8/B	TL	W11 W10 W9	325 12.8	1154 45.4	525 20.7	3423 134.8	0.8	2300	1500	1230	1070	1000	1000
								12	5070	3300	2710	2360	2200	2200
								1	2620	1710	1400	1220	1140	1140
								15	5770	3770	3080	2690	2510	2510
								1.3	3060	2000	1640	1420	1330	1330
								19	6740	4410	3610	3130	2930	2930
								1.6	3450	2250	1850	1610	1500	1500
								23	7600	4960	4070	3550	3300	3300

All tires confirms ETRTO T&RA & STRO standards