

FARMAX R80

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg / lbs					
480/80R42	151 A8/B	TL	DW16L	485 19.1	1835 72.2	848 33.4	5472 216.3	0.8	5290	3450	2830	2460	2300	2300
								12	11650	7600	6230	5420	5070	5070
								1	6030	3930	3220	2800	2620	2620
								15	13280	8660	7090	6170	5770	5770
								1.3	7040	4590	3760	3270	3060	3060
								19	15510	10110	8280	7200	6740	6740
								1.6	7940	5180	4240	3690	3450	3450
23	17490	11410	9340	8130	7600	7600								