

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				psi	16	25	31	40	psi	6	9
480/65R28	136 D	TL	W15L W14L	480 18.9	1335 52.6	608 23.9	3962 156	0.8	1710	1770	1630	1560	1490	1	2530	2310
								12	3770	3900	3590	3440	3280	15	5570	5090
								1	1960	2010	1860	1790	1700	1.3	2890	2640
								15	4320	4430	4100	3940	3740	18	6370	5810
								1.3	2280	2350	2170	2080	1980	1.6	3370	3070
								19	5020	5180	4780	4580	4360	24	7420	6760
								1.6	2580	2650	2450	2350	2240	2	3810	3470
								23	5680	5840	5400	5180	4930	29	8390	7640

All tires confirms ETRTO T&RA & STRO standards