

# FARMAX RC

**FEATURES**

- High lug angle at centre
- More overlap at centre

**BENEFITS**

- Better roadability
- Better stability

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Soil and plant protection

**FEATURE**

- Deep tread pattern

**BENEFIT**

- Long service life




**FEATURES**

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

**BENEFITS**

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm in	mm in					mm in	mm in	bar psi	6	16	25
230/95R44	129D/ 132A8	TL	W7 W8	228 9	1556 61.3	735 28.9	4812 189.5	2.8	1840	2400	1900	1750	1680	1600	1460
								41	4050	5290	4190	3850	3700	3520	3220
								3.2	1990	2600	2050	1890	1820	1730	1570
								46	4380	5730	4520	4160	4010	3810	3460
								3.6	2130	2780	2190	2030	1940	1850	1680
								52	4690	6120	4820	4470	4270	4070	3700

All tires confirms ETRTO T&RA & STRO standards