

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm	mm					6	16	25	31	40	50
				in	in				Recommend load kg /lbs						
320/90R42	136D/ 139A8	TL	W9 W10 W11	319 12.6	1643 64.7	764 30.1	4950 194.9	1.8	2170	2840	2240	2070	1980	1890	1720
								26	4780	6260	4930	4560	4360	4160	3790
								2	2310	3020	2380	2200	2110	2010	1830
								29	5090	6650	5240	4850	4650	4430	4030
								2.2	2450	3200	2520	2330	2240	2130	1940
								32	5400	7050	5550	5130	4930	4690	4270
								2.4	2580	3360	2650	2450	2350	2240	2040
								35	5680	7400	5840	5400	5180	4930	4490