

# FARMAX RC

**FEATURES**

- High lug angle at centre
- More overlap at centre

**BENEFITS**

- Better roadability
- Better stability

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Soil and plant protection

**FEATURE**

- Deep tread pattern

**BENEFIT**

- Long service life




**FEATURES**

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

**BENEFITS**

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm	mm					6	16	25	31	40	50
				in	in					Recommend load kg / lbs					
230/95R36	127D/ 130A8	TL	W7 W8	228 9	1352 53.2	633 24.9	4015 158.1	2.8	1630	2130	1680	1550	1490	1420	1290
								41	3590	4690	3700	3410	3280	3130	2840
								3.6	1900	2480	1960	1810	1730	1650	1500
								52	4190	5460	4320	3990	3810	3630	3300
								4	2010	2630	2070	1920	1840	1750	1590
								58	4430	5790	4560	4230	4050	3850	3500