

ELEVETA



FEATURE

- Specially designed for heavy duty forklift service

BENEFIT

- Excellent durability

FEATURE

- Superior tread compound

BENEFIT

- High resistance to wear, tear & cuts

FEATURE

- Alternate continuous lugs with high contact area

BENEFIT

- Maximum stability and load distribution

FEATURE

- Strong nylon casing

BENEFIT

- High load carrying capacity

MACHINERY



Forklift

Size	LI/SS	Type	PR	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Load capacity												
					SW	OD				Lift Truck				Side loader		Other Vehicle						
										Steering wheel		Load wheel										
										Speed Km/h/ mph												
										Static		25	35	10	25	50						
				mm	mm	mm	mm	bar	16	22	16	22	15	22	5	15	30					
				in	in	in	in	psi	1500	1390	1950	1875	2265	1500	1390	1950	1500	1260				
				7	23	11	69	112	3305	3065	4300	4135	4995	3305	3065	4300	3305	2780				
				Recommended Load kg/lbs																		
6.50-10	122A5	TT	10	5.00F	177	588	267	1740	7.75	1500	1390	1950	1875	2265	1500	1390	1950	1500	1260			

Also available in sizes: 6.00-9/6.90-9, 7.00-12, 8.25-15
All tires confirms ETRTO T&RA & STRO standards