

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
				mm/in	mm/in					25	40	50	65	bar psi	10	15
650/ 65R42	170D	TL	W18, DW20BL DW21B	645	1913	885	5775	2.4	5840	6020	5560	5330	5080	3	8640	7870
				25.4	75.3			35	12860	13260	12250	11740	11190	44	19030	17330
								2.8	6390	6590	6090	5840	5560	3.50	9450	8620
								41	14070	14520	13410	12860	12250	51	20810	18990
								3.0	6660	6860	6340	6080	5790	3.75	9840	8970
								44	14670	15110	13960	13390	12750	54	21670	19760
								3.2	6900	7110	6570	6300	6000	3.9875	10200	9300
								46	15200	15660	14470	13880	13220	58	22470	20480

All tires confirms ETRTO T&RA & STRO standards