

# FARMAX R85

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
520/85R46	174 A8/B	TL	DW16L DW18L	530 20.9	2052 80.8	939 37	6109 240.5	2.4	11430	7460	6110	5320	4970	4970
								35	25180	16430	13460	11720	10950	10950
								2.8	12510	8160	6690	5820	5440	5440
								41	27560	17970	14740	12820	11980	11980
								3.2	13520	8820	7230	6290	5880	5880
								46	29780	19430	15930	13850	12950	12950
								4	15410	10050	8240	7170	6700	6700
								58	33940	22140	18150	15790	14760	14760