

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
									Static	25	40	50	65	bar	10	15
				mm	mm				16	25	31	40	psi	6	9	
540/65R28	149D	TL	W16L W18L	550 21.7	1312 51.7	590 23	3860 152	1.4	2730	2810	2600	2490	2370	1.75	4030	3670
								20	6010	6190	5730	5480	5220	25	8880	8080
								1.6	2940	3030	2800	2690	2560	2	4350	3970
								23	6480	6670	6170	5930	5640	29	9580	8740
								2	3360	3460	3200	3070	2920	2.5	4960	4530
								29	7400	7620	7050	6760	6430	36	10930	9980
								2.4	3740	3850	3560	3410	3250	3	5530	5040
								35	8240	8480	7840	7510	7160	44	12180	11100