

# FARMAX R70

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded dimension		SLR	RC	Infl. Press	Speed, km/h (mph)					
			SW	OD				Static	10	20	30	40	50
			mm/in	mm/in					6	12	19	25	31
710/70R38	178A8/B	DW 23 B DW 25 B	715 28.15	1959 77.13	881 34.67	5785 227.8	2.6	15270	9960	8170	7100	6640	6640
							38	33630	21940	18000	15640	14630	14630
							2.8	15940	10400	8520	7420	6930	6930
							41	35110	22910	18770	16340	15260	15260
							3	16610	10830	8880	7730	7220	7220
							44	36590	23850	19560	17030	15900	15900
							3.2	17250	11250	8330	8030	7500	7500
							46	38000	24780	18350	17690	16520	16520