

FARMAX R85

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded dimension		SLR	RC	Infl. Press	Speed, km/h (mph)					
			SW	OD				Static	10	20	30	40	50
			mm/in	mm/in					6	12	19	25	31
380/80R38	152A8/B	W11 W12 W13	380 15	1573 61.9	757 29.8	4793 188.7	bar	maximum Load, kg (lbs)					
							psi						
							2.8	6620	4320	3540	3080	2880	2880
							41	14580	9520	7800	6780	6340	6340
							3	6900	4500	3690	3210	3000	3000
							44	15200	9910	8130	7070	6610	6610
							3.2	7180	4680	3840	3340	3120	3120
							46	15810	10310	8460	7360	6870	6870
							3.6	7680	5010	4110	3570	3340	3340
							52	16920	11040	9050	7860	7360	7360
4	8170	5330	4370	3800	3550	3550							
58	18000	11740	9630	8370	7820	7820							