

# TORQUEMAX

**FEATURE**

- Stepped lug design

**BENEFIT**

- Better Grip

**FEATURE**

- Tilted lug tip

**BENEFIT**

- Lower vibration at high speeds.

**FEATURE**

- Strong & wider lugs

**BENEFIT**

- Provides higher contact area leading to higher life



**FEATURE**

- Wider tread width

**BENEFIT**

- Lower Compaction

**FEATURE**

- Lower lug angle at the shoulder

**BENEFIT**

- Better traction

**FEATURE**


- Rounder shoulder

**BENEFIT**

- Lesser soil/crop damage

\*Lower Compaction, Higher Traction and Better Roadability

## MACHINERY



### Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					Tractor application						
		mm/in	mm/in					speed symbol	bar psi	Field Operation	10	20	30	40
480/80R50	DW15L DW16L	485 19.1	2038 80.2	950 37.4	6082 239.5	159D 162A8	0.8	5290	3450	2830	2650	2520	2420	2300
							12	11650	7600	6230	5840	5550	5330	5070
							1.2	6720	4380	3590	3360	3200	3070	2920
							17	14800	9650	7910	7400	7050	6760	6430
							1.6	7940	5180	4240	3970	3780	3620	3450
							23	17490	11410	9340	8740	8330	7970	7600
							1.8	8510	5550	4550	4260	4050	3890	3700
							26	18740	12220	10020	9380	8920	8570	8150
							2	9040	5900	4830	4520	4300	4130	3930
							29	19910	13000	10640	9960	9470	9100	8660
							2.4	10060	6560	5380	5030	4790	4590	4375
							35	22160	14450	11850	11080	10550	10110	9640

All tires confirms ETRTO T&RA & STRO standards