

FARMAX HPT



FEATURE

- Tilted lug tip

BENEFIT

- Reduced vibration

FEATURE

- Increased lug width

BENEFIT

- Provides longer service life

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE

- Wide tread width

BENEFIT

- Lower Compaction


FEATURE

- Rounder shoulder

BENEFIT

- Reduced soil disturbance

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)											
		SW	OD					Speed, km/h (mph)											
		Tractor application							Field Operation	10	20	30	40	50	65				
		mm/in	mm/in					mm/in								mm/in	speed symbol	bar psi	
480/80R50	DW15L	485	2038	950	6082	159D/162A8	0.8	5290	3450	2830	2650	2520	2420	2300					
							12	11650	7600	6230	5840	5550	5330	5070					
	1.2						6720	4380	3590	3360	3200	3070	2920						
	1.7						14800	9650	7910	7400	7050	6760	6430						
	1.6						7940	5180	4240	3970	3780	3620	3450						
	2.3						17490	11410	9340	8740	8330	7970	7600						
	1.8						8510	5550	4550	4260	4050	3890	3700						
	2.6						18740	12220	10020	9380	8920	8570	8150						
	2						9040	5900	4830	4520	4300	4130	3930						
	2.9						19910	13000	10640	9960	9470	9100	8660						
	2.4						10060	6560	5380	5030	4790	4590	4375						
	3.5						22160	14450	11850	11080	10550	10110	9640						

All tires confirms ETRTO T&RA & STRO standards