

TORQUEMAX

FEATURE

- Tilted lug tip

BENEFIT

- Lesser vibration and noise

FEATURE

- Mud breaker

BENEFIT

- Better self cleaning

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability



FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

FEATURE

- Rounded shoulder

BENEFIT

- Lesser damage to soil and crop

FEATURES


- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction

*Lower Compaction, Higher Traction and Better Roadability

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs) Speed, km/h (mph)								
		SW	OD					MIXED APPLICATION								
		mm / in	mm / in					mm / in	mm / in	Speed	bar	Satatic	10	20	30	40
						Symbol	psi									
480/80R50	DW15L DW16L	485 19.1	2038 80.2	950 37.4	6082 239.5	159D 162A8	0.8	5290	3450	2830	2650	2520	2420	2300		
							12	11650	7600	6230	5840	5550	5330	5070		
							1.2	6720	4380	3590	3360	3200	3070	2920		
							17	14800	9650	7910	7400	7050	6760	6430		
							1.6	7940	5180	4240	3970	3780	3620	3450		
							23	17490	11410	9340	8740	8330	7970	7600		
							1.8	8510	5550	4550	4260	4050	3890	3700		
							26	18740	12220	10020	9380	8920	8570	8150		
							2	9040	5900	4830	4520	4300	4130	3930		
							29	19910	13000	10640	9960	9470	9100	8660		
2.4	10060	6560	5380	5030	4790	4590	4375									
35	22160	14450	11850	11080	10550	10110	9640									

All tires confirms ETRTO T&RA & STRO standards