

TORQUEMAX

FEATURE

- Tilted lug tip

BENEFIT

- Lesser vibration and noise

FEATURE

- Mud breaker

BENEFIT

- Better self cleaning

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability



FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

FEATURE

- Rounded shoulder

BENEFIT

- Lesser damage to soil and crop


FEATURES

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction

MACHINERY



Tractor

*Lower Compaction, Higher Traction and Better Roadability

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	PR, Load Index	Infl. Press	Recommend load, kg (lbs)					
		Speed, km/h (mph)											
		MIXED APPLICATION											
		mm / in	mm / in	mm / in	mm / in	Speed	bar	Satatic	10	30	40	50	65
						Symbol	psi						
480/80R50	DW15L DW16L	485 19.1	2038 80.2	950 37.4	6082 239.5	165D 168A8	0.8	5270	3440	2630	2510	2400	2290
							12	11610	7580	5790	5530	5290	5040
							1.2	6670	4350	3340	3180	3050	2900
							17	14690	9580	7360	7000	6720	6390
							1.6	7890	5150	3940	3760	3600	3430
							23	17380	11340	8680	8280	7930	7560
							1.8	8460	5520	4230	4030	3860	3680
							26	18630	12160	9320	8880	8500	8110
							2	8990	5870	4500	4280	4110	3910
							29	19800	12930	9910	9430	9050	8610
							3.2	11850	7730	5920	5640	5410	5150
							46	26100	17030	13040	12420	11920	11340

All tires confirms ETRTO T&RA & STRO standards