

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded dimension		SLR	RC	Infl. Press	Speed, km/h (mph)						
			SW	OD				Static	10	25	40	50	65	70
			mm/in	mm/in					6	15	25	31	40	43
710/70R42	173D/176A8	DW 23 B DW 25 B	715 28.1	2061 81.1	932 36.7	6119 240.9	1.8	12630	8240	6510	6010	5760	5490	5000
							26	27820	18150	14340	13240	12690	12090	11010
							2	13430	8760	6920	6390	6130	5840	5310
							29	29580	19300	15240	14070	13500	12860	11700
							2.2	14210	9270	7320	6770	6490	6180	5620
							32	31300	20420	16120	14910	14300	13610	12380
							2.4	14950	9750	7700	7120	6830	6500	5920
							35	32930	21480	16960	15680	14320	16520	13040