

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	PR, Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm / in	mm / in					Field	10	25	40	50	65	70
320/90R50	W10 W9 W11	325 12.8	1846 72.7	867 34.1	5576 219.5	150D/ 153A8	bar							
							psi							
							3	3320	4340	3420	3160	3030	2890	2630
							41	7310	9560	7530	6960	6670	6370	5790
							3.0	3460	4520	3570	3300	3160	3010	2740
							44	7620	9960	7860	7270	6960	6630	6040
							3	3730	4860	3840	3550	3400	3240	2950
							49	8220	10700	8460	7820	7490	7140	6500
4	3850	5030	3970	3670	3520	3350	3050							
52	8480	11080	8740	8080	7750	7380	6720							

All tires confirms ETRTO T&RA & STRO standards