

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	PR, Load Index	Infl. Press	Recommend load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm / in	mm / in					Field	10	25	40	50	65	70	
380/90R50 (14.9 R 50)	W12 W11 W13	390 15.4	1954 76.9	918 36.1	5951 234.3	158D/161A8	bar								
							psi								
							2	3360	4380	3460	3200	3070	2920	2660	
							35	7400	9650	7620	7050	6760	6430	5860	
							3	3670	4790	3780	3490	3350	3190	2900	
							41	8080	10550	8330	7690	7380	7030	6390	
							3	3970	5180	4090	3780	3620	3450	3140	
							46	8740	11410	9010	8330	7970	7600	6920	
4	4890	6380	5040	4650	4460	4250	3870								
52	10770	14050	11100	10240	9820	9360	8520								

All tires confirms ETRTO T&RA & STRO standards