

# FARMAX RC

**FEATURES**

- High lug angle at centre
- More overlap at centre

**BENEFITS**

- Better roadability
- Better stability

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Soil and plant protection

**FEATURE**

- Deep tread pattern

**BENEFIT**

- Long service life




**FEATURES**

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

**BENEFITS**

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

## MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	PR, Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm / in	mm / in					Field	10	25	40	50	65	70
230/95R40	W8 W7	228 9.0	1454 57.2	684 26.9	4385 172.6	132D/ 135A8	2.8	1990	2600	2050	1890	1820	1730	1570
							41	4380	5730	4520	4160	4010	3810	3460
							3.2	2150	2810	2220	2050	1960	1870	1700
							46	4740	6190	4890	4520	4320	4120	3740
							3.6	2300	3000	2370	2190	2100	2000	1820
							52	5070	6610	5220	4820	4630	4410	4010
							3.6	2300	3000	2370	2190	2100	2000	1820
							52	5070	6610	5220	4820	4630	4410	4010