

TORQUEMAX

FEATURE

- Tilted lug tip

BENEFIT

- Lesser vibration and noise

FEATURE

- Mud breaker

BENEFIT

- Better self cleaning

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability



FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

FEATURE

- Rounded shoulder

BENEFIT

- Lesser damage to soil and crop

FEATURES


- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction

*Lower Compaction, Higher Traction and Better Roadability

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs) Speed, km/h (mph)						
		SW	OD					MIXED APPLICATION				CYCLIC*		
		mm	mm					10	20	30	40 to 65	70	15	30
IF 520/85R38	DW20 DW18	526 20.7	1849 72.8	841 33.1	5518 217.3	167D	0.8	3630	3090	2970	2860	2600	3290	3130
							12	8000	6810	6540	6300	5730	7250	6890
							1.2	4610	3920	3780	3630	3300	4170	3970
							17	10150	8630	8330	8000	7270	9190	8740
							1.6	5460	4640	4470	4300	3910	4950	4710
							23	12030	10220	9850	9470	8610	10900	10370
							2	6220	5290	5100	4900	4460	5640	5370
							29	13700	11650	11230	10790	9820	12420	11830
							2.2	6580	5590	5390	5180	4710	5960	5670
							32	14490	12310	11870	11410	10370	13130	12490
							2.4	6920	5890	5670	5450	4960	6270	5970
							35	15240	12970	12490	12000	10930	13810	13150