

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	PR, Stars Load Index	Infl. Press	Maximum load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm / in	mm / in					mm / in	mm / in	mm / in	mm / in	mm / in	mm / in	mm / in	
300/95R52 (12.4 R 52)	W9, W10	300 11.8	1891 74.4	892 35.1	5792 228.0	149D/152A8	Speed	bar	field	10	25	40	50	65	70
							Symbol	psi	6	16	25	31	40	43	
							0.8	1470	1920	1520	1410	1340	1280	1160	
							12	3240	4230	3350	3110	2950	2820	2560	
							1.2	1860	2430	1920	1780	1700	1620	1470	
							17	4100	5350	4230	3920	3740	3570	3240	
							1.8	2360	3080	2430	2260	2150	2050	1870	
							26	5200	6780	5350	4980	4740	4520	4120	
							2.4	2780	3630	2870	2660	2540	2420	2200	
							35	6120	8000	6320	5860	5590	5330	4850	
							2.8	3050	3980	3140	2920	2780	2650	2410	
							41	6720	8770	6920	6430	6120	5840	5310	
							3.2	3290	4290	3390	3150	3000	2860	2600	
							46	7250	9450	7470	6940	6610	6300	5730	
							3.6	3520	4590	3630	3370	3210	3060	2780	
52	7750	10110	8000	7420	7070	6740	6120								
4	3740	4880	3850	3580	3410	3250	2960								
58	8240	10750	8480	7890	7510	7160	6520								

All tires confirms ETRTO T&RA & STRO standards