

YIELDMAX



FEATURE

- R1-W Pattern

BENEFIT

- Longer tyre life

FEATURE

- Dual Lug angle

BENEFIT

- Higher traction and better stability

FEATURE

- Higher lug overlap

BENEFIT

- Enhanced road ability and load ability

FEATURE

- Strong & sharp shoulders

BENEFIT

- Better grip

FEATURE

- Wide open shoulders

BENEFIT

- Better self cleaning


FEATURE

- Rounded Lug Base

BENEFIT

- Stubble Resistance

MACHINERY



Harvester

*Lower Compaction, Higher Traction and Better Roadability

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	Load Index	Infl. press.	Recommended load, kg (lbs)							Cyclic operation	
		SW	OD					Speed, km/h (mph)								
		mm	mm					MIXED APPLICATION								
								in	in	10	20	30	40	50	10	15
650/75R32	DW21B DW20L	625 24.6	1810 71.3	857 33.7	5459 214.9	172A8/B	2	10370	6770	5550	4830	4510	4510	8120	7440	
							26	22840	14910	12220	10640	9930	9930	17890	16390	
							2	11660	7610	6240	5420	5070	5070	9130	8370	
							32	25680	16760	13740	11940	11170	11170	20110	18440	
							2	12260	8000	6560	5700	5330	5330	9590	8790	
							35	27000	17620	14450	12560	11740	11740	21120	19360	
							3	13410	8750	7170	6240	5830	5830	10490	9620	
							41	29540	19270	15790	13740	12840	12840	23110	21190	
							3	13960	9110	7470	6490	6070	6070	10930	10020	
							44	30750	20070	16450	14300	13370	13370	24070	22070	
							3	14490	9450	7750	6740	6300	6300	11340	10400	
							46	31920	20810	17070	14850	13880	13880	24980	22910	

All tires confirms ETRTO T&RA & STRO standards