

FLOATMAX FT

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life


FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)					
		SW mm in	OD mm in	Radius mm in	mm in	Speed Symbol		Speed, km/h (mph)					
								MIXED APPLICATION					
								Static	10	30	40	50	65
500	AG16.00	503	1172	530	3571	155D	1.2	4390	3440	2880	2600	2310	1910
60R22.5		19.8	46.1	20.9	140.6	155D	17	9670	7580	6340	5730	5090	4210
							1.6	5200	4070	3410	3070	2730	2260
							23	11450	8960	7510	6760	6010	4980
							2.4	6600	5170	4330	3900	3470	2870
							35	14540	11390	9540	8590	7640	6320
							2.8	7220	5650	4740	4270	3800	3140
							41	15900	12440	10440	9410	8370	6920
							3.6	8370	6550	5500	4950	4400	3640
							52	18440	14430	12110	10900	9690	8020
							4	8910	6980	5850	5270	4690	3875
							58	19630	15370	12890	11610	10330	8540