

# TORQUEMAX



**FEATURE**

- Stepped lug design

**BENEFIT**

- Better Grip

**FEATURE**

- Tilted lug tip

**BENEFIT**

- Lower vibration at high speeds.

**FEATURE**

- Strong & wider lugs

**BENEFIT**

- Provides higher contact area leading to higher life

**FEATURE**

- Wider tread width

**BENEFIT**

- Lower Compaction

**FEATURE**

- Lower lug angle at the shoulder

**BENEFIT**

- Better traction

**FEATURE**


- Rounder shoulder

**BENEFIT**

- Lesser soil/crop damage

\*Lower Compaction, Higher Traction and Better Roadability

## MACHINERY



### Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
		mm/in	mm/in					Tractor application					
		mm/in	mm/in					speed symbol	bar psi	Field Operation	10	30	40
480/80R50	DW15L DW16L	485 19.1	2038 80.2	950 37.4	6082 239.5	165D 168A8	0.8	5270	3440	2630	2510	2400	2290
							12	11610	7580	5790	5530	5290	5040
							1.2	6670	4350	3340	3180	3050	2900
							1.7	14690	9580	7360	7000	6720	6390
							1.6	7890	5150	3940	3760	3600	3430
							2.3	17380	11340	8680	8280	7930	7560
							1.8	8460	5520	4230	4030	3860	3680
							2.6	18630	12160	9320	8880	8500	8110
							2	8990	5870	4500	4280	4110	3910
							2.9	19800	12930	9910	9430	9050	8610
							3.2	11850	7730	5920	5640	5410	5150
							4.6	26100	17030	13040	12420	11920	11340

All tires confirms ETRTO T&RA & STRO standards