

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE


- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

*Lower Compaction i er traction and Better Roadability

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					Tractor application						
		mm/in	mm/in					speed symbol	bar psi	Field Operation	10	20	30	40
650/85R38	DW23B, DW21B, DW20B	675 26.6	2071 81.5	947 37	6181 243	170D 173A8	0.8	3930	5130	4210	3930	3740	3590	3420
							12	8660	11300	9270	8660	8240	7910	7530
							1.2	4980	6500	5330	4980	4740	4550	4330
							17	10970	14320	11740	10970	10440	10020	9540
							1.6	5890	7680	6300	5890	5610	5380	5120
							23	12970	16920	13880	12970	12360	11850	11280
							1.8	6300	8220	6740	6300	6000	5750	5480
							26	13880	18110	14850	13880	13220	12670	12070
							2.1	6900	9000	7750	6900	6570	6300	6000
30	15200	19820	17070	15200	14470	13880	13220							